

Title: Czyszczenie bazy danych przed uruchomieniem

Subject: Archiwum - eDokumenty - elektroniczny system obiegu dokumentów, workflow i CRM -
DeployerGuide/Others/DatabaseCleanup

Version: 18

Date: 06/21/26 15:19:42

Table of Contents

Czyszczenie bazy danych przed uruchomieniem

3

Czyszczenie bazy danych przed uruchomieniem

Po okresie testowania klient życzy sobie aby wyczyścić bazę. Można to zrobić poprzez wywołanie odpowiednich komend w bazie danych.

```
-- wyczyszczenie tabel z rekordami dziennikow
delete from regofpapers ;
delete from regofvatnotes;
delete from regofmagazins;
delete from regofresolutions;
delete from regofnotes;

-- wyczyszczenie tabel dokumentow
delete from documents;
delete from documents_history;
delete from attachments;

-- wyzerowanie liczników
update counters set cntval = 0;
update briefcases set countr = 0;
update doss_extract_list set countr = 0;

-- wyczyszczenie zdarzen
delete from rcp_cards;
delete from events;
delete from process_comments;
delete from process_participants;
delete from processes;
delete from proc_link_users;

-- czyczczenie etapów, procedur
delete from stages;
delete from procedures;

-- czyszczenie usuniętych wpisów
DELETE from fk_elements WHERE doc_id IN (SELECT doc_id FROM documents where adduid IN (SELECT usr_id FROM users where is_d

delete from documents where adduid IN (SELECT usr_id FROM users where is_del is true);

delete from rcp_cards WHERE emp_id IN(SELECT usr_id FROM users where is_del is true);

delete from readed_comments where usr_id IN (SELECT usr_id FROM users where is_del is true);

delete from contacts_caretakers where usr_id IN (SELECT usr_id FROM users where is_del is true);

delete from vindication.vind_proc where vindyc IN (SELECT usr_id FROM users where is_del is true);

DELETE from fk_elements WHERE adduid IN (SELECT usr_id FROM users where is_del is true);

delete from users where is_del is true;

delete from rcp_cards WHERE prc_id IN(select prc_id from processes where is_del is true);

delete from fk_elements WHERE prc_id IN(select prc_id from processes where is_del is true);

delete from process_participants WHERE prc_id IN(select prc_id from processes where is_del is true);

delete from processes where is_del is true;

delete FROM organization_units WHERE is_del IS TRUE;

delete from fk_elements WHERE doc_id IN(SELECT doc_id FROM documents where is_del is true);
```

```
delete from documents where is_del is true;  
  
delete from log;
```

Po testach procedur również można wyczyścić instancje procedur :

```
DELETE FROM procedures WHERE NOT EXISTS (SELECT d.procid FROM documents d WHERE p.procid = d.procid AND d.procid IS NOT NULL)  
NOT EXISTS (SELECT d.procid FROM processes d WHERE p.procid = d.procid AND d.procid IS NOT NULL) AND  
NOT EXISTS (SELECT d.procid FROM rcp_cards d WHERE p.procid = d.procid AND d.procid IS NOT NULL)
```

Policzyć można je za pomocą:

```
SELECT count(procid) FROM procedures p WHERE NOT EXISTS (SELECT d.procid FROM documents d WHERE p.procid = d.procid AND d.  
NOT EXISTS (SELECT d.procid FROM processes d WHERE p.procid = d.procid AND d.procid IS NOT NULL) AND  
NOT EXISTS (SELECT d.procid FROM rcp_cards d WHERE p.procid = d.procid AND d.procid IS NOT NULL)
```