

Title: The Trac Configuration File

Subject: eDokumenty - elektroniczny system obiegu dokumentów, workflow i CRM - TracIni

Version: 1

Date: 02/04/26 09:10:43

Table of Contents

| | |
|------------------------------------|----|
| <i>The Trac Configuration File</i> | 3 |
| <i>Global Configuration</i> | 3 |
| <i>Reference</i> | 3 |
| <i>[addheaders]</i> | 3 |
| <i>[attachment]</i> | 3 |
| <i>[browser]</i> | 3 |
| <i>[changeset]</i> | 4 |
| <i>[header_logo]</i> | 4 |
| <i>[inherit]</i> | 4 |
| <i>[logging]</i> | 5 |
| <i>[milestone]</i> | 5 |
| <i>[mimeviewer]</i> | 5 |
| <i>[notification]</i> | 5 |
| <i>[project]</i> | 6 |
| <i>[query]</i> | 7 |
| <i>[report]</i> | 7 |
| <i>[revisionlog]</i> | 7 |
| <i>[roadmap]</i> | 7 |
| <i>[search]</i> | 7 |
| <i>[sqlite]</i> | 7 |
| <i>[svn]</i> | 8 |
| <i>[ticket]</i> | 8 |
| <i>[timeline]</i> | 8 |
| <i>[trac]</i> | 9 |
| <i>[versioncontrol]</i> | 11 |
| <i>[wiki]</i> | 11 |
| <i>[wikiprint]</i> | 11 |
| <i>[components]</i> | 11 |
| <i>[ticket-custom]</i> | 12 |
| <i>[ticket-workflow]</i> | 12 |
| <i>[milestone-groups]</i> | 12 |
| <i>[svn:externals]</i> | 12 |

The Trac Configuration File

Global Configuration

In versions prior to 0.11, the global configuration was by default located in `$prefix/share/trac/conf/trac.ini` or sometimes `/etc/trac/trac.ini` depending on the distribution. If you're upgrading, you may want to specify that file to inherit from.

Global options will be merged with the environment-specific options, where local options override global options. The options file is specified as follows:

```
[inherit]
file = /usr/share/trac/conf/trac.ini
```

Note that you can also specify a global option file when creating a new project, by adding the option `--inherit=/path/to/global/options` to [trac-admin's initenv](#) command. If you would not do this but nevertheless intend to use a global option file with your new environment, you would have to go through the newly generated `conf/trac.ini` file and delete the entries that would otherwise override those set in the global file.

Reference

This is a brief reference of available configuration options.

[addheaders]

| | |
|---------------------|--|
| add_links | |
| add_metas | |
| add_scripts | |
| add_styles | |
| default_base | |
| default_meta_lang | |
| default_script_base | |
| default_style_base | |

[attachment]

| | |
|-----------------------|---|
| max_size | Maximum allowed file size (in bytes) for ticket and wiki attachments. |
| render_unsafe_content | Whether attachments should be rendered in the browser, or only made downloadable. Pretty much any file may be interpreted as HTML by the browser, which allows a malicious user to attach a file containing cross-site scripting attacks. For public sites where anonymous users can create attachments it is recommended to leave this option disabled (which is the default). |

[browser]

| | |
|--------------------|--|
| color_scale | Enable colorization of the age column. This uses the same color scale as the source code annotation: blue is older, red is newer. (since 0.11) |
| downloadable_paths | List of repository paths that can be downloaded. Leave the option empty if you want to disable all downloads, otherwise set it to a comma-separated list of authorized paths (those paths are glob patterns, i.e. "*" can be used as a wild card) (since 0.10) |
| hide_properties | Comma-separated list of version control properties to hide from the repository browser. (since 0.9) |

| | |
|-----------------------|---|
| intermediate_color | (r,g,b) color triple to use for the color corresponding to the intermediate color, if two linear interpolations are used for the color scale (see <code>intermediate_point</code>). If not set, the intermediate color between <code>oldest_color</code> and <code>newest_color</code> will be used. (since 0.11) |
| intermediate_point | If set to a value between 0 and 1 (exclusive), this will be the point chosen to set the <code>intermediate_color</code> for interpolating the color value. (since 0.11) |
| newest_color | (r,g,b) color triple to use for the color corresponding to the newest color, for the color scale used in <code>blame</code> or the browser <code>age</code> column if <code>color_scale</code> is enabled. (since 0.11) |
| oldest_color | (r,g,b) color triple to use for the color corresponding to the oldest color, for the color scale used in <code>blame</code> or the browser <code>age</code> column if <code>color_scale</code> is enabled. (since 0.11) |
| oneliner_properties | Comma-separated list of version control properties to render as oneliner wiki content in the repository browser. (since 0.11) |
| render_unsafe_content | Whether raw files should be rendered in the browser, or only made downloadable. Pretty much any file may be interpreted as HTML by the browser, which allows a malicious user to create a file containing cross-site scripting attacks. For open repositories where anyone can check-in a file, it is recommended to leave this option disabled (which is the default). |
| wiki_properties | Comma-separated list of version control properties to render as wiki content in the repository browser. (since 0.11) |

[changeset]

| | |
|----------------------|--|
| max_diff_bytes | Maximum total size in bytes of the modified files (their old size plus their new size) for which the changeset view will attempt to show the diffs inlined (since 0.10). |
| max_diff_files | Maximum number of modified files for which the changeset view will attempt to show the diffs inlined (since 0.10). |
| wiki_format_messages | Whether wiki formatting should be applied to changeset messages. If this option is disabled, changeset messages will be rendered as pre-formatted text. |

[header_logo]

| | |
|--------|---|
| alt | Alternative text for the header logo. |
| height | Height of the header logo image in pixels. |
| link | URL to link to, from the header logo. |
| src | URL of the image to use as header logo. It can be absolute, server relative or relative. If relative, it is relative to one of the <code>/chrome</code> locations: <code>site/your-logo.png</code> if <code>your-logo.png</code> is located in the <code>htdocs</code> folder within your TracEnvironment ; <code>common/your-logo.png</code> if <code>your-logo.png</code> is located in the folder mapped to the htdocs_location URL. Only specifying <code>your-logo.png</code> is equivalent to the latter. |
| width | Width of the header logo image in pixels. |

[inherit]

| | |
|-------------|---|
| plugins_dir | Path to the <i>shared plugins</i> directory. Plugins in that directory are loaded in addition to those in the directory of the environment <code>plugins</code> , with this one taking precedence. (since 0.11) |
|-------------|---|

| | |
|---------------|---|
| templates_dir | Path to the <i>shared templates directory</i> . Templates in that directory are loaded in addition to those in the environments templates directory, but the latter take precedence. (since 0.11) |
|---------------|---|

[logging]

| | |
|------------|--|
| log_file | If log_type is <code>file</code> , this should be a path to the log-file. Relative paths are resolved relative to the <code>log</code> directory of the environment. |
| log_format | Custom logging format. If nothing is set, the following will be used: Trac[\$(module)s] \$(levelname)s: \$(message)s In addition to regular key names supported by the Python logger library (see http://docs.python.org/library/logging.html), one could use: - \$(path)s the path for the current environment - \$(basename)s the last path component of the current environment - \$(project)s the project name Note the usage of \$(...)s instead of %(...)s as the latter form would be interpreted by the ConfigParser itself. Example: \$(thread)d Trac[\$(basename)s:\$(module)s] \$(levelname)s: \$(message)s (since 0.10.5) |
| log_level | Level of verbosity in log. Should be one of (CRITICAL, ERROR, WARN, INFO, DEBUG). |
| log_type | Logging facility to use. Should be one of (none, file, stderr, syslog, winlog). |

[milestone]

| | |
|----------------|--|
| stats_provider | Name of the component implementing <code>ITicketGroupStatsProvider</code> , which is used to collect statistics on groups of tickets for display in the milestone views. |
|----------------|--|

[mimereviewer]

| | |
|------------------------|---|
| max_preview_size | Maximum file size for HTML preview. (since 0.9) |
| mime_map | List of additional MIME types and keyword mappings. Mappings are comma-separated, and for each MIME type, there's a colon (":") separated list of associated keywords or file extensions. (since 0.10) |
| pygments_default_style | The default style to use for Pygments syntax highlighting. |
| pygments_modes | List of additional MIME types known by Pygments. For each, a tuple <code>mimetype:mode:quality</code> has to be specified, where <code>mimetype</code> is the MIME type, <code>mode</code> is the corresponding Pygments mode to be used for the conversion and <code>quality</code> is the quality ratio associated to this conversion. That can also be used to override the default quality ratio used by the Pygments render. |
| tab_width | Displayed tab width in file preview. (since 0.9) |
| treat_as_binary | Comma-separated list of MIME types that should be treated as binary data. (since 0.11.5) |

[notification]

| | |
|------------------------|---|
| admit_domains | Comma-separated list of domains that should be considered as valid for email addresses (such as <code>localdomain</code>). |
| always_notify_owner | Always send notifications to the ticket owner (since 0.9). |
| always_notify_reporter | Always send notifications to any address in the <code>reporter</code> field. |
| always_notify_updater | Always send notifications to the person who causes the ticket property change and to any previous updater of that ticket. |

| | |
|-------------------------|---|
| ambiguous_char_width | Which width of ambiguous characters (e.g. 'single' or 'double') should be used in the table of notification mail. If 'single', the same width as characters in US-ASCII. This is expected by most users. If 'double', twice the width of US-ASCII characters. This is expected by CJK users. (since 0.12.2) |
| email_sender | Name of the component implementing <code>IEmailSender</code> . This component is used by the notification system to send emails. Trac currently provides <code>SmtpEmailSender</code> for connecting to an SMTP server, and <code>SendmailEmailSender</code> for running a sendmail-compatible executable. (since 0.12) |
| ignore_domains | Comma-separated list of domains that should not be considered part of email addresses (for usernames with Kerberos domains). |
| mime_encoding | Specifies the MIME encoding scheme for emails. Valid options are 'base64' for Base64 encoding, 'qp' for Quoted-Printable, and 'none' for no encoding, in which case mails will be sent as 7bit if the content is all ASCII, or 8bit otherwise. (since 0.10) |
| sendmail_path | Path to the sendmail executable. The sendmail program must accept the -i and -f options. (since 0.12) |
| smtp_always_bcc | Email address(es) to always send notifications to, addresses do not appear publicly (Bcc:). (since 0.10). |
| smtp_always_cc | Email address(es) to always send notifications to, addresses can be seen by all recipients (Cc:). |
| smtp_default_domain | Default host/domain to append to address that do not specify one. |
| smtp_enabled | Enable email notification. |
| smtp_from | Sender address to use in notification emails. |
| smtp_from_name | Sender name to use in notification emails. |
| smtp_password | Password for SMTP server. (since 0.9) |
| smtp_port | SMTP server port to use for email notification. |
| smtp_replyto | Reply-To address to use in notification emails. |
| smtp_server | SMTP server hostname to use for email notifications. |
| smtp_subject_prefix | Text to prepend to subject line of notification emails. If the setting is not defined, then the <code>[\$project_name]</code> prefix. If no prefix is desired, then specifying an empty option will disable it. (since 0.10.1) |
| smtp_user | Username for SMTP server. (since 0.9) |
| ticket_subject_template | A Genshi text template snippet used to get the notification subject. By default, the subject template is <code>\$prefix #\$ticket.id: \$summary</code> . <code>\$prefix</code> being the value of the <code>smtp_subject_prefix</code> option. (since 0.11) |
| use_public_cc | Recipients can see email addresses of other CC'ed recipients. If this option is disabled (the default), recipients are put on BCC. (since 0.10) |
| use_short_addr | Permit email address without a host/domain (i.e. username only). The SMTP server should accept those addresses, and either append a FQDN or use local delivery. (since 0.10) |
| use_tls | Use SSL/TLS to send notifications over SMTP. (since 0.10) |

[project]

| | |
|-------|--|
| admin | E-Mail address of the project's administrator. |
|-------|--|

| | |
|----------------|--|
| admin_trac_url | Base URL of a Trac instance where errors in this Trac should be reported. This can be an absolute or relative URL, or '.' to reference this Trac instance. An empty value will disable the reporting buttons. (since 0.11.3) |
| descr | Short description of the project. |
| footer | Page footer text (right-aligned). |
| icon | URL of the icon of the project. |
| name | Name of the project. |
| url | URL of the main project web site, usually the website in which the base_url resides. This is used in notification e-mails. |

[query]

| | |
|-------------------------|--|
| default_anonymous_query | The default query for anonymous users. The query is either in query language syntax, or a URL query string starting with ? as used in query: Trac links . (since 0.11.2) |
| default_query | The default query for authenticated users. The query is either in query language syntax, or a URL query string starting with ? as used in query: Trac links . (since 0.11.2) |
| items_per_page | Number of tickets displayed per page in ticket queries, by default (since 0.11) |
| ticketlink_query | The base query to be used when linkifying values of ticket fields. The query is a URL query string starting with ? as used in query: Trac links . (since 0.12) |

[report]

| | |
|--------------------|---|
| items_per_page | Number of tickets displayed per page in ticket reports, by default (since 0.11) |
| items_per_page_rss | Number of tickets displayed in the rss feeds for reports (since 0.11) |

[revisionlog]

| | |
|-------------------|---|
| default_log_limit | Default value for the limit argument in the TracRevisionLog (since 0.11). |
|-------------------|---|

[roadmap]

| | |
|----------------|---|
| stats_provider | Name of the component implementing ITicketGroupStatsProvider , which is used to collect statistics on groups of tickets for display in the roadmap views. |
|----------------|---|

[search]

| | |
|--------------------------|---|
| default_disabled_filters | Specifies which search filters should be disabled by default on the search page. This will also restrict the filters for the quick search function. The filter names defined by default components are: wiki, ticket, milestone and changeset. For plugins, look for their implementation of the ISearchSource interface, in the <code>get_search_filters()</code> method, the first member of returned tuple. Once disabled, search filters can still be manually enabled by the user on the search page. (since 0.12) |
| min_query_length | Minimum length of query string allowed when performing a search. |

[sqlite]

| | |
|------------|--|
| extensions | Paths to sqlite extensions, relative to Trac environment's directory or absolute. (since 0.12) |
|------------|--|

[svn]

| | |
|----------|--|
| branches | Comma separated list of paths categorized as branches. If a path ends with '*', then all the directory entries found below that path will be included. Example: /trunk, /branches/*, /projectAlpha/trunk, /sandbox/* |
| tags | Comma separated list of paths categorized as tags. If a path ends with '*', then all the directory entries found below that path will be included. Example: /tags/*, /projectAlpha/tags/A-1.0, /projectAlpha/tags/A-v1.1 |

[ticket]

| | |
|----------------------|---|
| default_cc | Default cc: list for newly created tickets. |
| default_component | Default component for newly created tickets. |
| default_description | Default description for newly created tickets. |
| default_keywords | Default keywords for newly created tickets. |
| default_milestone | Default milestone for newly created tickets. |
| default_owner | Default owner for newly created tickets. |
| default_priority | Default priority for newly created tickets. |
| default_resolution | Default resolution for resolving (closing) tickets (since 0.11). |
| default_severity | Default severity for newly created tickets. |
| default_summary | Default summary (title) for newly created tickets. |
| default_type | Default type for newly created tickets (since 0.9). |
| default_version | Default version for newly created tickets. |
| max_comment_size | Don't accept tickets with a too big comment. (since 0.11.2) |
| max_description_size | Don't accept tickets with a too big description. (since 0.11). |
| preserve_newlines | Whether Wiki formatter should respect the new lines present in the Wiki text. If set to 'default', this is equivalent to 'yes' for new environments but keeps the old behavior for upgraded environments (i.e. 'no'). (since 0.11). |
| restrict_owner | Make the owner field of tickets use a drop-down menu. Be sure to understand the performance implications before activating this option. See Assign-to as Drop-Down List . Please note that e-mail addresses are not obfuscated in the resulting drop-down menu, so this option should not be used if e-mail addresses must remain protected. (since 0.9) |
| workflow | Ordered list of workflow controllers to use for ticket actions (since 0.11). |

[timeline]

| | |
|---------------------------|---|
| abbreviated_messages | Whether wiki-formatted event messages should be truncated or not. This only affects the default rendering, and can be overridden by specific event providers, see their own documentation. (Since 0.11) |
| changeset-collapse_events | Whether consecutive changesets from the same author having exactly the same message should be presented as one event. That event will link to the range of changesets in the log view. (since 0.11) |

| | |
|-------------------------|---|
| changeset_long_messages | Whether wiki-formatted changeset messages should be multiline or not. If this option is not specified or is false and <code>wiki_format_messages</code> is set to true, changeset messages will be single line only, losing some formatting (bullet points, etc). |
| changeset_show_files | Number of files to show (-1 for unlimited, 0 to disable). This can also be location, for showing the common prefix for the changed files. (since 0.11). |
| default_daysback | Default number of days displayed in the Timeline, in days. (since 0.9.) |
| max_daysback | Maximum number of days (-1 for unlimited) displayable in the Timeline. (since 0.11) |
| newticket_formatter | Which formatter flavor (e.g. 'html' or 'oneliner') should be used when presenting the description for new tickets. If 'oneliner', the <code>[timeline] abbreviated_messages</code> option applies. (since 0.11). |
| ticket_show_details | Enable the display of all ticket changes in the timeline, not only open / close operations (since 0.9). |

[trac]

| | |
|----------------------|--|
| auth_cookie_lifetime | Lifetime of the authentication cookie, in seconds. This value determines how long the browser will cache authentication information, and therefore, after how much inactivity a user will have to log in again. The default value of 0 makes the cookie expire at the end of the browsing session. (since 0.12) |
| auth_cookie_path | Path for the authentication cookie. Set this to the common base path of several Trac instances if you want them to share the cookie. (since 0.12) |
| authz_file | The path to the Subversion authorization (authz) file . To enable authz permission checking, the <code>AuthzSourcePolicy</code> permission policy must be added to <code>[trac] permission_policies</code> . |
| authz_module_name | The module prefix used in the <code>authz_file</code> for the default repository. If left empty, the global section is used. |
| auto_preview_timeout | Inactivity timeout in seconds after which the automatic wiki preview triggers an update. This option can contain floating-point values. The lower the setting, the more requests will be made to the server. Set this to 0 to disable automatic preview. The default is 2.0 seconds. (since 0.12) |
| auto_reload | Automatically reload template files after modification. |
| backup_dir | Database backup location |
| base_url | Reference URL for the Trac deployment. This is the base URL that will be used when producing documents that will be used outside of the web browsing context, like for example when inserting URLs pointing to Trac resources in notification e-mails. |
| check_auth_ip | Whether the IP address of the user should be checked for authentication (since 0.9). |
| database | Database connection string for this project |
| debug_sql | Show the SQL queries in the Trac log, at DEBUG level. (Since 0.11.5) |
| default_charset | |
| default_handler | Name of the component that handles requests to the base URL. Options include <code>TimelineModule</code> , <code>RoadmapModule</code> , <code>BrowserModule</code> , <code>QueryModule</code> , <code>ReportModule</code> , <code>TicketModule</code> and <code>WikiModule</code> . The default is <code>WikiModule</code> . (since 0.9) |
| default_language | The preferred language to use if no user preference has been set. (since 0.12.1) |

| | |
|-----------------------------|---|
| default_timezone | The default timezone to use |
| genshi_cache_size | The maximum number of templates that the template loader will cache in memory. The default value is 128. You may want to choose a higher value if your site uses a larger number of templates, and you have enough memory to spare, or you can reduce it if you are short on memory. |
| htdocs_location | Base URL for serving the core static resources below /chrome/common/. It can be left empty, and Trac will simply serve those resources itself. Advanced users can use this together with trac-admin ... deploy <code><deploydir></code> to allow serving the static resources for Trac directly from the web server. Note however that this only applies to the <code><deploydir>/htdocs/common</code> directory, the other deployed resources (i.e. those from plugins) will not be made available this way and additional rewrite rules will be needed in the web server. |
| ignore_auth_case | Whether login names should be converted to lower case (<i>since 0.9</i>). |
| mainnav | Order of the items to display in the mainnav navigation bar, listed by IDs. See also TracNavigation . |
| metanav | Order of the items to display in the metanav navigation bar, listed by IDs. See also TracNavigation . |
| mysqldump_path | Location of mysqldump for MySQL database backups |
| never_obfuscate_mailto | Never obfuscate mailto: links explicitly written in the wiki, even if show_email_addresses is false or the user has not the EMAIL_VIEW permission (<i>since 0.11.6</i>). |
| permission_policies | List of components implementing <code>IPermissionPolicy</code> , in the order in which they will be applied. These components manage fine-grained access control to Trac resources. Defaults to the <code>DefaultPermissionPolicy</code> (pre-0.11 behavior) and <code>LegacyAttachmentPolicy</code> (map <code>ATTACHMENT_*</code> permissions to realm specific ones) |
| permission_store | Name of the component implementing <code>IPermissionStore</code> , which is used for managing user and group permissions. |
| pg_dump_path | Location of pg_dump for Postgres database backups |
| repository_dir | Path to the default repository. This can also be a relative path (<i>since 0.11</i>). This option is deprecated, and repositories should be defined in the repositories section, or using the "Repositories" admin panel. (<i>since 0.12</i>) |
| repository_sync_per_request | List of repositories that should be synchronized on every page request. Leave this option empty if you have set up post-commit hooks calling <code>trac-admin \$ENV changeset</code> added on all your repositories (recommended). Otherwise, set it to a comma-separated list of repository names. Note that this will negatively affect performance, and will prevent changeset listeners from receiving events from the repositories specified here. The default is to synchronize the default repository, for backward compatibility. (<i>since 0.12</i>) |
| repository_type | Default repository connector type. (<i>since 0.10</i>) This is also used as the default repository type for repositories defined in TracIni#repositories-section repositories or using the "Repositories" admin panel. (<i>since 0.12</i>) |
| request_filters | Ordered list of filters to apply to all requests (<i>since 0.10</i>). |
| resizable_textareas | Make <code><textarea></code> fields resizable. Requires JavaScript. (<i>since 0.12</i>) |
| secure_cookies | Restrict cookies to HTTPS connections. When true, set the secure flag on all cookies so that they are only sent to the server on HTTPS connections. Use this if your Trac instance is only accessible through HTTPS. (<i>since 0.11.2</i>) |

| | |
|---------------------------|--|
| show_email_addresses | Show email addresses instead of usernames. If false, we obfuscate email addresses. (since 0.11) |
| show_ip_addresses | Show IP addresses for resource edits (e.g. wiki). (since 0.11.3) |
| timeout | Timeout value for database connection, in seconds. Use '0' to specify <i>no timeout</i> . (Since 0.11) |
| use_base_url_for_redirect | Optionally use [trac] base_url for redirects. In some configurations, usually involving running Trac behind a HTTP proxy, Trac can't automatically reconstruct the URL that is used to access it. You may need to use this option to force Trac to use the base_url setting also for redirects. This introduces the obvious limitation that this environment will only be usable when accessible from that URL, as redirects are frequently used. (since 0.10.5) |

[versioncontrol]

| | |
|---------------------------------|--|
| allowed_repository_dir_prefixes | Comma-separated list of allowed prefixes for repository directories when adding and editing repositories in the repository admin panel. If the list is empty, all repository directories are allowed. (since 0.12.1) |
|---------------------------------|--|

[wiki]

| | |
|-----------------------|---|
| ignore_missing_pages | Enable/disable highlighting CamelCase links to missing pages (since 0.9). |
| max_size | Maximum allowed wiki page size in bytes. (since 0.11.2) |
| render_unsafe_content | Enable/disable the use of unsafe HTML tags such as <script> or <embed> with the HTML WikiProcessor (since 0.10.4). For public sites where anonymous users can edit the wiki it is recommended to leave this option disabled (which is the default). |
| safe_schemes | List of URI schemes considered "safe", that will be rendered as external links even if [wiki] render_unsafe_content is false. (since 0.11.8) |
| split_page_names | Enable/disable splitting the WikiPageNames with space characters (since 0.10). |

[wikiprint]

| | |
|-------------------|--|
| article_css_url | |
| book_css_url | |
| css_url | |
| extracontent_url | |
| frontpage_url | |
| httpauth_password | |
| httpauth_user | |
| omit_links | |
| omit_macros | |
| rebase_links | |
| toc_title | |

[components]

This section is used to enable or disable components provided by plugins, as well as by Trac itself. The component to enable/disable is specified via the name of the option. Whether its enabled is determined by the option value; setting the value to enabled or on will enable the component, any other

value (typically `disabled` or `off`) will disable the component.

The option name is either the fully qualified name of the components or the module/package prefix of the component. The former enables/disables a specific component, while the latter enables/disables any component in the specified package/module.

Consider the following configuration snippet:

```
[components]
trac.ticket.report.ReportModule = disabled
webadmin.* = enabled
```

The first option tells Trac to disable the [report module](#). The second option instructs Trac to enable all components in the `webadmin` package. Note that the trailing wildcard is required for module/package matching.

See the [Plugins](#) page on [About Trac](#) to get the list of active components (requires `CONFIG_VIEW` [permissions](#).)

See also: [TracPlugins](#)

[ticket-custom]

In this section, you can define additional fields for tickets. See [TracTicketsCustomFields](#) for more details.

[ticket-workflow]

(*since 0.11*)

The workflow for tickets is controlled by plugins. By default, there's only a `ConfigurableTicketWorkflow` component in charge. That component allows the workflow to be configured via this section in the `trac.ini` file. See [TracWorkflow](#) for more details.

[milestone-groups]

(*since 0.11*)

As the workflow for tickets is now configurable, there can be many ticket states, and simply displaying closed tickets vs. all the others is maybe not appropriate in all cases. This section enables one to easily create *groups* of states that will be shown in different colors in the milestone progress bar.

Example configuration (which is also the default):

```
closed = closed
closed.order = 0                      # sequence number in the progress bar
closed.query_args = group=resolution # optional extra param for the query
closed.overall_completion = true      # count for overall completion

active = *                            # one catch-all group is allowed
active.order = 1
active.css_class = open               # CSS class for this interval
active.label = in progress           # Displayed label for this group
```

The definition consists in a comma-separated list of accepted status. Also, `**` means any status and could be used to associate all remaining states to one catch-all group.

The CSS class can be one of: `new` (yellow), `open` (no color) or `closed` (green). New styles can easily be added using the following selector:
`table.progress td.<class>`

[svn:externals]

(*since 0.11*)

The [TracBrowser](#) for Subversion can interpret the `svn:externals` property of folders out of the box. However, if those externals are *not* using the `http:` protocol, or if a link to a different repository browser (such another Trac or [ViewVC](#)) is desired, then Trac needs to be able to map an external prefix to this other URL.

This mapping is done in the [svn:externals] section of the [TracIni](#)

Example:

```
[svn:externals]
1 = svn://server/repos1 http://trac/proj1/browser/$path?rev=$rev
2 = svn://server/repos2 http://trac/proj2/browser/$path?rev=$rev
3 = http://theirserver.org/svn/eng-soft http://ourserver/viewvc/svn/$path/?pathrev=25914
4 = svn://anotherserver.com/tools_repository http://ourserver/trac/support/browser/$path?rev=$rev
```

With the above, the svn://anotherserver.com/tools_repository/tags/1.1/tools external will be mapped to <http://ourserver/trac/support/browser/tags/1.1/tools?rev=> (and rev will be set to the appropriate revision number if the external additionally specifies a revision, see the [SVN Book on externals](#) for more details).

Note that the number used as a key in the above section is purely used as a place holder, as the URLs themselves can't be used as a key due to various limitations in the configuration file parser.

See also: [TracGuide](#), [TracAdmin](#), [TracEnvironment](#)